


NASA/CR-2000-209868



Fuel Plume Image Mixing Analysis Formulation With Proper Treatment of Non-Constant Velocity Flowfields

Gregory L. Mekkes
Federal Data Corporation, Hampton, Virginia

March 2000

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:


- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart or peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.
- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- Email your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Telephone the NASA STI Help Desk at (301) 621-0390
- Write to:
NASA STI Help Desk
NASA Center for AeroSpace Information
7121 Standard Drive
Hanover, MD 21076-1320

NASA/CR-2000-209868



Fuel Plume Image Mixing Analysis Formulation With Proper Treatment of Non-Constant Velocity Flowfields

Gregory L. Mekkes
Federal Data Corporation, Hampton, Virginia

National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23681-2199

Prepared for Langley Research Center
under Contract NAS1-96013

March 2000

Acknowledgments

The author gratefully acknowledges the original foundation for this work established by R. Clayton Rogers of the NASA Langley Research Center.

Available from:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 605-6000

Abstract

A previously developed technique allows an estimate of integral mixing to be obtained from an image of laser scattered light from particle seeded fuel in the hypervelocity flow through a scramjet combustor. This previous mixing analysis formulation contains an assumption of a constant velocity flowfield across the plane of the fuel plume image. For high-speed scramjet combustors, the velocity flowfield is quite uniform and an assumption of constant velocity works well. Applying this same mixing analysis technique to fuel plume images obtained from a mid-speed scramjet combustor makes it desirable to remove the constant velocity assumption. This is due to the non-uniform velocity flowfields present in mid-speed scramjet combustors. A new formulation of the mixing analysis methodology is developed and presented so that the technique can be applied to a mid-speed scramjet combustor without the need to assume a constant velocity flowfield.

Nomenclature

A	Area	W	Molecular weight
f	Fuel-air mass ratio	X	Distance from fuel injection location
H	Fuel injector ramp height	Y	Mass fraction
I	Image intensity	η_M	Mixing efficiency parameter
\dot{m}	Mass flow rate	ρ	Mass density
N	Number density	τ	Image exposure time
N_A	Avogadro's number	ϕ	Fuel equivalence ratio
U	Local velocity		

Subscripts

C	Camera	ROI	Region of Interest
f	Fuel	RX	Reactable
L	Laser	ST	Stoichiometric

Introduction

The objective of scramjet combustor ground tests is to acquire data useful in quantifying the performance of the modeled scramjet. Key to performance is the fuel mixing achieved within the combustor, which can be deduced from flowfield data. One way to achieve this result is to acquire fuel concentration distributions within the fuel plume structure through the use of fuel plume imaging. Image data obtained in this manner can be processed to yield an estimate of the integral fuel mixing. Initially this technique was applied to high-speed scramjet combustors and the analysis method utilized an assumption of constant velocity across the plane of the fuel plume image [1]. The purpose of the current work is to extend the range of applicability of fuel plume image mixing analysis to include mid-speed scramjet combustors, for which the velocity flowfield is much less uniform and cannot be assumed to be con-

stant. A reformulated fuel plume image mixing analysis method is developed and presented along with guidelines to help determine which method of analysis is appropriate.

Fuel Plume Imaging

Fuel plume imaging relies on Mie scattering from particle seeded fuel which is illuminated by a sheet of light optically formed from a laser beam. References 1, 2, and 3 contain specific details concerning optimization of operational parameters for the purpose of obtaining clean fuel plume images. Basically, silica spheres are used to seed the fuel prior to injection. It is assumed that the seed particles are uniformly distributed and that they track the flow direction accurately. A pulsed laser is set up so that the beam forms a sheet of light which passes through the combustor test section perpendicular to the direction of flow. The laser light sheet is assumed to be of uniform intensity and thickness. Finally a high resolution digital camera is used to capture an image from the laser light scattered by the seed particles, resulting in a fuel plume image. The assumptions of uniform particle distribution, particle flow tracking, and laser light sheet uniformity are reasonable assumptions which are discussed in more detail in the above mentioned references.

Image Processing

Fuel plume imaging is a non-intrusive procedure. As a result, the camera view angle is such that the raw image will need perspective and optical corrections. As a basis for performing these corrections, a grid block with uniform squares marked out on the surface is typically used. This grid block can be placed at the same location and orientation as the laser light sheet, and then imaged by the same camera which is used to obtain the fuel plume images. By doing this, known image locations from the grid block image can be used to properly alter the perspective and optical distortion of the fuel plume image.

After correcting for perspective and optical distortion, the region of interest must then be extracted from the fuel plume image. Ideally the region of interest would encompass the entire combustor cross section shape. In reality, laser sheet wall and window interference and reflection patterns can render sections of the image unusable. Also, silica particles can agglomerate on the walls and windows creating increased or additional interference patterns. Even so, it is possible at times to obtain fuel plume images which are clean enough to use the entire combustor cross section as the region of interest. Typically an area immediately surrounding a single fuel plume or group of plumes is used as the region of interest.

When the region of interest has been extracted from the perspective corrected fuel plume image, a determination must be made of the intensity range which constitutes presence of zero fuel. This is accomplished by looking at the intensity values in locations clearly outside of the fuel plume structure and identifying the maximum intensity from the ambient background. Once this maximum ambient intensity has been identified, all image intensity values in the extracted region of interest are modified so that values ranging from zero to the ambient background maximum are reset to a value of zero. All other values are proportionally stretched to fill in the range of $I=1$ to the maximum image intensity. Typical fuel plume images are obtained as 8-bit monochrome images for which the maximum intensity range is $I=0$ to $I=255$. A raw fuel plume image will usually not span the entire range of possible intensities, so this image intensity modification will actually increase the apparent dynamic range of the image, but this will not affect the correctness or accuracy of the calculated mixing efficiency. A processed fuel plume image from which a mixing efficiency will be calculated must have the image intensity range modified so that an intensity of zero corresponds to zero fuel.

Each individual fuel plume image will have unique subtleties. In some images there may be small areas of interference possibly caused by particle agglomeration on the optical window. If these areas are small and few, it is possible to utilize either an image filtering process or a photo-retouching process to allow the region of interest to include areas which would otherwise be unusable. In some instances, this could allow information to be extracted from an image which would have otherwise been entirely unusable.

Mixing Analysis

Based on the assumptions outlined above pertaining to uniform particle distribution, particle flow tracking, and laser light sheet uniformity, it can be subsequently assumed that fuel plume image intensity is proportional to seed particle number density, N , when taking particle velocity and image exposure time into account.

$$I_{\text{IMAGE}} = C_0 N U \tau \quad \text{where} \quad N = \frac{N_A}{W_f} \rho Y_f \quad (1)$$

C_0 is a constant along with the image exposure time, τ , which represents minimum time duration of either the laser pulse, τ_L , or camera shutter speed, τ_C . U represents a known velocity distribution across the plane of the fuel plume image. Since a non-constant velocity distribution will affect the apparent particle number density, the fuel plume image must be processed to take this into account.

$$I = \frac{I_{\text{IMAGE}}}{U} \quad \text{so that} \quad I = C_1 N \quad \text{where} \quad C_1 = C_0 \tau \quad (2)$$

If the velocity distribution is assumed to be constant or is unknown and must be assumed to be constant, then the following relationships are used.

$$I = I_{\text{IMAGE}} \quad \text{so that} \quad I = C_1 N \quad \text{where} \quad C_1 = C_0 U \tau \quad (3)$$

At this point, either equation set (2) or equation set (3) can be substituted into equation set (1) to yield the same result.

$$I = C_1 \frac{N_A}{W_f} \rho Y_f \quad (4)$$

Since both Avogadro's number, N_A , and the fuel molecular weight, W_f , are constant, equation (4) can be expressed as follows.

$$I = C_2 \rho Y_f \quad \text{where} \quad C_2 = C_1 \frac{N_A}{W_f} \quad (5)$$

Using the average velocity over the region of interest, \bar{U} , which is constant by definition, yields the following.

$$I = C_3 \rho \bar{U} Y_f \quad \text{where} \quad C_3 = \frac{C_2}{\bar{U}} \quad (6)$$

Integrating the fuel plume image intensity over the area of the region of interest results in the following.

$$I_{\text{TOTAL}} = \int_{\text{ROI}} I \, dA = C_3 \int_{\text{ROI}} \rho \bar{U} Y_f \, dA = C_3 \dot{m}_f \quad (7)$$

Using the definition of the fuel-air mass ratio yields the following relationship.

$$\dot{m}_f = f \dot{m}_{\text{air}} = f (\rho \bar{U} A_{\text{ROI}} - \dot{m}_f) \quad (8)$$

Rearranging equation (8) yields the following.

$$(1 + f) \dot{m}_f = f \rho \bar{U} A_{\text{ROI}} \quad \text{and} \quad \dot{m}_f = \frac{f}{1 + f} \rho \bar{U} A_{\text{ROI}} \quad (9)$$

Substituting equation set (9) into equation set (7) produces the following.

$$I_{\text{TOTAL}} = C_3 \dot{m}_f = C_3 \frac{f}{1 + f} \rho \bar{U} A_{\text{ROI}} = C_3 \rho \bar{U} \bar{Y}_f A_{\text{ROI}} \quad (10)$$

The quantity $\rho \bar{U}$ represents the average mass flux over the region of interest, which is constant by definition. Next, the average intensity over the region of interest is defined as follows.

$$\bar{I}_{\text{ROI}} = \frac{I_{\text{TOTAL}}}{A_{\text{ROI}}} = C_4 \frac{f}{1 + f} = C_4 \bar{Y}_f \quad \text{where} \quad C_4 = C_3 \rho \bar{U} \quad (11)$$

Using equation set (11) allows the constant C_4 to be redefined using known and obtainable values.

$$\bar{I}_{\text{ROI}} = C_4 \bar{Y}_f \quad \text{and in general} \quad I = C_4 Y_f \quad \text{where} \quad C_4 = \frac{\bar{I}_{\text{ROI}}}{\left(\frac{f}{1 + f}\right)} \quad (12)$$

Next, assume a linear relationship between \bar{I}_{ROI} and I_{ST} such that at $\phi = 1$, $I_{\text{ST}} = \bar{I}_{\text{ROI}}$.

$$\bar{I}_{\text{ROI}} = \phi I_{\text{ST}} \quad \text{or} \quad I_{\text{ST}} = \frac{\bar{I}_{\text{ROI}}}{\phi} \quad (13)$$

The implication inherent in this assumption is that the processed fuel plume image intensities have been modified so that $I=0$ corresponds to zero fuel.

Over the region of interest, for $I \leq I_{ST}$, $\int IdA$ is proportional to that part of \dot{m}_f which is fuel lean and entirely reactable. For $I > I_{ST}$ in the region of interest, the reactable mass fraction is estimated by the following relationship.

$$I_{RX} = C_4 Y_{RX} = C_4 f_{ST}(1 - Y_f) \quad \text{where} \quad Y_f = \frac{I}{C_4} \quad (14)$$

Therefore, in the region of interest, for $I > I_{ST}$, $\int I_{RX} dA$ is proportional to that part of \dot{m}_f which is fuel rich and can react only to the extent of available air. Previously [1], this integration has been performed as a linear approximation between two points, $I=I_{ST}$ and $I=I_{MAX}$. With this formulation, it is recommended to perform the integration at each discrete intensity value. One additional consideration for this integration is that the upper limit intensity can be no more than a value of $I = C_4$. Any fuel plume image intensities above this value would numerically supply negative reactable fuel to the integration process. This would indicate some non-physical aspect to the processed fuel plume image.

The definition of mixing efficiency is the following [1,4].

$$\eta_M = \frac{\int \rho U Y_{RX} dA}{\dot{m}_{RX}} \quad \text{where} \quad Y_{RX} = \begin{cases} Y_f & \text{for } \phi \leq 1 \\ f_{ST}(1 - Y_f) & \text{for } \phi > 1 \end{cases} \quad \text{and} \quad \dot{m}_{RX} = \begin{cases} \dot{m}_f & \text{for } \phi \leq 1 \\ f_{ST} \dot{m}_{air} & \text{for } \phi > 1 \end{cases} \quad (15)$$

By definition, $\phi = f/f_{ST}$ and $f_{ST} = f/\phi$, therefore $f_{ST} \dot{m}_{air} = (f/\phi) \dot{m}_{air} = \dot{m}_f/\phi$. Substituting this relationship into the appropriate portion of equation set (15) provides the following.

$$\dot{m}_{RX} = \begin{cases} \dot{m}_f & \text{for } \phi \leq 1 \\ \dot{m}_f/\phi & \text{for } \phi > 1 \end{cases} \quad (16)$$

Using equation set (7) along with the definition of mixing efficiency contained in equation sets (15) and (16) allows mixing efficiency to be directly calculated from the information contained in a fuel plume image.

$$\eta_M = \begin{cases} \left[\frac{\left(\int_{LEAN} IdA + \int_{RICH} I_{RX} dA \right)}{\int_{ROI} IdA} \right] & \text{for } \phi \leq 1 \\ \left[\frac{\phi \left(\int_{LEAN} IdA + \int_{RICH} I_{RX} dA \right)}{\int_{ROI} IdA} \right] & \text{for } \phi > 1 \end{cases} \quad (17)$$

In arriving at equation (17), note that it is not necessary to be able to obtain a known value for the constant C_3 . This is due to the fact that it appears in both the numerator and denominator of equation (17). An additional implication of this is that the spanned intensity range of the processed fuel plume image does not affect the calculation of a mixing efficiency as long as $I=0$ corresponds to zero fuel.

Results and Discussion

The first two fuel plume images were acquired from a Mach 2 scramjet combustor test which represented a mid-speed combustor at a flight enthalpy of Mach 5 [5]. These images were both taken at the $X/H=6$ location, where the full test section size is $6H$ wide by $4H$ tall. Figures 1 and 2 show the unprocessed fuel plume images, which were both acquired during one test. It should be noted that these images do not encompass the entire test section, but do include the entire fuel plume. The result of applying the image processing steps to these raw fuel plume images is shown in Figures 3 and 4. These processed fuel plume images will be referred to as image 1 and image 2.




Figure 1. Unprocessed fuel plume image 1




Figure 2. Unprocessed fuel plume image 2




Figure 3. Processed fuel plume image 1




Figure 4. Processed fuel plume image 2

A CFD solution is used to provide velocity field information for use with these fuel plume images [5]. The velocity field at the $X/H=6$ location is shown in Figure 5 with the outlined area representing the extent of the processed fuel plume images. Figures 3 and 4 contain the result of applying the velocity correction to images 1 and 2 respectively. It is found that within the fuel plume, velocity ranges from approximately 100 to 1400 m/sec. As a result, it appears that an assumption of constant velocity would not work well for mixing analysis of these images. To gain more insight into this matter, it is necessary to look at the range of particle travel distances captured in the images. Acquisition of these images involved a pulsed laser which formed a sheet approximately 1 mm thick. The limiting factor for the image exposure time was the laser pulse duration such that $\tau = \tau_L = 7$ nanoseconds. As a result, the particle travel distances captured in these fuel plume images range from 0.0007 to 0.0098 laser sheet thick-

nesses. Velocity non-uniformity is not an issue in these fuel plume images, which are essentially instantaneous images rather than time averaged images. Consequently, even though these fuel plume images are taken from a mid-speed combustor with significant velocity non-uniformity, an assumption of constant velocity is appropriate.




Figure 5. Velocity field at X/H=6 with outline of processed fuel plume image area




Figure 6. Processed fuel plume image 1 with velocity correction applied




Figure 7. Processed fuel plume image 2 with velocity correction applied

Mixing analysis of images 1 and 2 was performed both with and without the constant velocity assumption as a basis of comparison between the two methods. For image 1, $\eta_M=23.85\%$ assuming constant velocity and $\eta_M=23.77\%$ with the velocity correction applied. For image 2, $\eta_M=23.90\%$ assuming constant velocity and $\eta_M=23.37\%$ with the velocity correction applied. Applying the constant velocity assumption, these two images exhibit closer agreement of the resultant mixing efficiency.

The next set of fuel plume images was obtained from a similar test in the same facility [2]. From this test, one image taken at X/H=6, image 3, will be analyzed along with an image taken at X/H=2, image 4. Computational velocity information is also available for these images. Figures 8-11 contain the processed fuel plume images both with and without velocity correction applied. Note that for this set of images, the raw fuel plume images did include the entire combustor cross section. And as a result, the

processed fuel plume images encompass the entire 6H by 4H test section, a much larger area than that of the previous set of processed images.




Figure 8. Processed fuel plume image 3




Figure 9. Processed fuel plume image 4



Figure 10. Processed fuel plume image 3 with velocity correction applied




Figure 11. Processed fuel plume image 4 with velocity correction applied

Images 3 and 4 were acquired using a continuous laser which formed a sheet that was 200 μ meters thick. The limiting factor for the image exposure time for these images was the camera exposure setting such that $\tau = \tau_C = 0.8$ seconds. For image 3, at $X/H=6$, velocity within the fuel plume ranges from 100 to 1000 m/sec. In image 4, at $X/H=2$, velocity within the fuel plume ranges from 1400 to 2200 m/sec. In terms of particle travel distances captured in these images, image 3 ranges from 0.4 million to 5.0 million laser sheet thicknesses, while image 4 ranges from 5.6 million to 8.8 million laser sheet thicknesses. These images provide time averaged representations of the fuel plume, and as a result, it is desirable to apply a velocity correction prior to calculating a mixing efficiency.

Mixing analysis of images 3 and 4 was also performed with and without the constant velocity assumption so that a comparison can be made between the two methods. For image 3, $\eta_M=15.02\%$ assuming constant velocity and $\eta_M=14.02\%$ with the velocity correction applied. For image 4, $\eta_M=5.63\%$ assuming constant velocity and $\eta_M=5.80\%$ with the velocity correction applied. Note that at $X/H=2$ there is less variation of velocity across the fuel plume than at $X/H=6$, and the resulting mixing efficiency quantities are closer in agreement at $X/H=2$ than those at $X/H=6$.

Table 1 provides a summary of results obtained from the mixing analysis of the four images presented above. Note that the fuel equivalence ratio is lower for images 3 and 4. As a result, it is not possible to make direct comparisons among images 1, 2, and 3 at $X/H=6$.

Table 1. Summary of mixing analysis results

Image	Type of Image	X/H	Velocity Correction	η_M (%)
1	Instantaneous	6	No	23.85
			Yes	23.77
2	Instantaneous	6	No	23.90
			Yes	23.37
3	Time Averaged	6	No	15.02
			Yes	14.02
4	Time Averaged	2	No	5.63
			Yes	5.80

Conclusions

When processing fuel plume images to calculate an estimate of mixing efficiency, a known velocity field is typically not available. Consequently, the assumption of a constant velocity must then be used. For fuel plume images obtained from tests of a mid-speed scramjet combustor, this constant velocity assumption appears to be a potential source of great error due to the non-uniform velocity fields present in mid-speed scramjet combustors. However, in looking closely at the mixing analysis formulation, it is based on integrations of the general form $\int I dA$. Also, as part of the image processing, areas with no fuel present will have an intensity value of zero. As a result, an integration of image intensity over area will accumulate nothing in areas of zero fuel. Effectively, this means that an assumption of constant velocity is really only an assumption of constant velocity within the fuel plume. Non-uniformity of velocity outside the fuel plume does not enter into the calculation of mixing efficiency.

If the velocity field is known when processing fuel plume images, mixing efficiency can be calculated both with and without the constant velocity assumption to verify the resulting difference in these values. A typical expectation is that the difference between these two values would be greater at locations closer to the fuel injectors. Certainly this would seem logical since the non-uniformity of velocity is greater across planes that are closer to the fuel injection location. In reality, it does not matter how uniform or non-uniform the velocity is across the entire plane. Locations closer to fuel injection provide greater velocity uniformity across the fuel plume. For mid-speed or high-speed scramjet combustor tests, fuel plume image mixing analysis with a constant velocity assumption will be more accurate for locations closer to fuel injection.

It is important to understand whether a fuel plume image represents an instantaneous image or a time averaged image of the fuel plume. An instantaneous image does not require a velocity correction to be applied since it has effectively been applied already due to the method of image acquisition. On the other hand, accuracy of fuel plume image mixing analysis can be improved for time averaged images by taking the velocity field into account. This accuracy improvement is greater in situations where the velocity non-uniformity across the fuel plume is greater.

Summary

For accurate mixing analysis of fuel plume images obtained from mid-speed scramjet combustor tests, two methods can be used to properly take into account the non-constant velocity flowfield. Fuel plume images can be acquired as instantaneous images and processed using the constant velocity assumption to arrive at an accurate estimate of mixing. And for time averaged fuel plume images, the presented mixing analysis formulation for non-constant velocity can be used to obtain an accurate estimate of mixing if flowfield velocity information is available.

References

1. Rogers, R.C.; Weidner, E.H.; and Bittner, R.D.: *Quantification of Scramjet Mixing in the Hypervelocity Flow of a Pulse Facility*. AIAA Paper 94-2518, June 1994.
2. Nicholson, Mark A.: *Fuel Plume Imaging in a Supersonic Combusting Flow*. Master of Science Thesis, University of Virginia, August 1995.
3. Tsai, C.Y.; Calleja, J.F.; Bakos, R.J.; and Rogers, R.C.: *A Technique for Mixing Measurement in Hypervelocity Pulse Facilities Using Particle Scattering Imagery*. AIAA Paper 96-2222, June 1996.
4. Rogers, R.C.: *Mixing of Hydrogen Injected from Multiple Injectors Normal to a Supersonic Airstream*. NASA TN D-6476, September 1971.
5. Goynes, C.P.; McDaniel, J.C.; Quagliaroli, T.M.; and Krauss, R.H.: *Dual-Mode Combustion of Hydrogen in a Mach 5 Enthalpy, Clean-Air, Continuous-Flow Facility*. ISABE Paper IS-145, September 1999.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 07704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE March 2000	3. REPORT TYPE AND DATES COVERED Contractor Report		
4. TITLE AND SUBTITLE Fuel Plume Image Mixing Analysis Formulation With Proper Treatment of Non-Constant Velocity Flowfields		5. FUNDING NUMBERS C NAS1-96013 WU 706-51-21-10		
6. AUTHOR(S) Gregory L. Mekkes				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Federal Data Corporation Mail Stop 186A NASA Langley Research Center Hampton VA 23681-2199		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Langley Research Center Hampton, VA 23681-2199		10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA/CR-2000-209868		
11. SUPPLEMENTARY NOTES Langley Technical Monitor: Charles R. McClinton				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 07 Availability: NASA CASI (301) 621-0390		12b. DISTRIBUTION CODE Distribution: Standard		
13. ABSTRACT (Maximum 200 words) A previously developed technique allows an estimate of integral mixing to be obtained from an image of laser scattered light from particle seeded fuel in the hypervelocity flow through a scramjet combustor. This previous mixing analysis formulation contains an assumption of a constant velocity flowfield across the plane of the fuel plume image. For high-speed scramjet combustors, the velocity flowfield is quite uniform and an assumption of constant velocity works well. Applying this same mixing analysis technique to fuel plume images obtained from a mid-speed scramjet combustor makes it desirable to remove the constant velocity assumption. This is due to the non-uniform velocity flowfields present in mid-speed scramjet combustors. A new formulation of the mixing analysis methodology is developed and presented so that the technique can be applied to a mid-speed scramjet combustor without the need to assume a constant velocity flowfield.				
14. SUBJECT TERMS Fuel plume image, laser scattered light, scramjet combustor, particle seeded fuel, mixing efficiency, laser sheet, image processing.		15. NUMBER OF PAGES 15		16. PRICE CODE A03
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	