


NASA/TM-2001-210877



MAVRIC Flutter Model Transonic Limit Cycle Oscillation Test

*John W. Edwards, David M. Schuster, Charles V. Spain, Donald F. Keller, and
Robert W. Moses
Langley Research Center, Hampton, Virginia*

May 2001

The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.


- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results ... even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Phone the NASA STI Help Desk at (301) 621-0390
- Write to:
NASA STI Help Desk
NASA Center for AeroSpace Information
7121 Standard Drive
Hanover, MD 21076-1320

NASA/TM-2001-210877



MAVRIC Flutter Model Transonic Limit Cycle Oscillation Test

*John W. Edwards, David M. Schuster, Charles V. Spain, Donald F. Keller, and
Robert W. Moses
Langley Research Center, Hampton, Virginia*

National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23681-2199

May 2001

Available from:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 605-6000

Abstract

The Models for Aeroelastic Validation Research Involving Computation semi-span wind-tunnel model (MAVRIC-I), a business jet wing-fuselage flutter model, was tested in NASA Langley's Transonic Dynamics Tunnel with the goal of obtaining experimental data suitable for Computational Aeroelasticity code validation at transonic separation onset conditions. This research model is notable for its inexpensive construction and instrumentation installation procedures. Unsteady pressures and wing responses were obtained for three wingtip configurations: clean, tipstore, and winglet. Traditional flutter boundaries were measured over the range of $M = 0.6$ to 0.9 and maps of Limit Cycle Oscillation (LCO) behavior were made in the range of $M = 0.85$ to 0.95 . Effects of dynamic pressure and angle-of-attack were measured. Testing in both R134a heavy gas and air provided unique data on Reynolds number, transition effects, and the effect of speed of sound on LCO behavior. The data set provides excellent code validation test cases for the important class of flow conditions involving shock-induced transonic flow separation onset at low wing angles, including Limit Cycle Oscillation behavior.

INTRODUCTION

The Models for Aeroelastic Validation Research Involving Computation (MAVRIC) project was undertaken by NASA Langley Research Center's Aeroelasticity Branch with the goal of obtaining experimental wind-tunnel data suitable for Computational Aeroelasticity (CAE) code validation at transonic separation onset conditions. The aeroelastic response behavior referred to as "Limit Cycle Oscillation" (LCO) is the primary target. LCO behavior is characterized by rather constant

amplitude, periodic structural response at selective frequencies which are usually recognizable as being those of the aeroelastically loaded structure. Bunton and Denegri¹ discuss LCO characteristics of fighter aircraft and Denegri² provides test cases from flight tests of the F-16 aircraft for three classes of response: Classical Flutter, Typical LCO, and Nontypical LCO, which are very well suited for use as computational test cases. Cunningham^{3,4} and Meijer^{5,6} also describe LCO experience on the F-16 aircraft and present results of semi-empirical modeling of the LCO phenomenon. While their formulation³⁻⁶ is general, the focus of the applications has been upon LCOs encountered between angles-of-attack of 5-10 degrees and involving interaction of leading-edge vortex flows, tip flows, and normal wing shocks. In contrast, the test cases of Ref. 2 are all for '1-g' level flight at transonic speeds where there are no leading-edge vortex flows. This brings into focus a key feature of LCO behavior: incidents of (aerodynamically induced) LCO are found for flow fields featuring transitions or boundaries between differing flow states. A prime example is the onset of

separated flow over some portion of an aircraft's lifting surfaces. Furthermore, the LCO is typically limited to a narrow region in Mach number and/or angle-of-attack signaling the change in flow state, such as separation onset. LCO occurrences are common on fighter aircraft; Norton⁷ describes incidents on F-5, F-16, F-111, F-15 STOL, and F/A-18 aircraft. LCOs induced by structural nonlinearities have been widely reported in the literature and are not considered in this paper.

Incidents of LCO are not limited to fighter aircraft. LCOs are reported by Jacobson, et al.⁸ and Dreim, et al.⁹ involving wing-bending interaction with rigid-body pitching and plunging on the B-2 bomber, and Edwards¹⁰ reports LCO behavior on a generic business jet wind-tunnel flutter model. Since LCO behavior is closely related to subcritical flutter behavior (e.g., aeroelastic response at speeds near but below the flutter speed, with the attendant very low damping levels), attempts to study the behavior with wind-tunnel flutter models have been made. The attempts are frequently unsuccessful due to lack of knowledge of the necessary ingredients producing LCO, the inability to fully simulate full-scale aircraft conditions in wind-tunnel testing (model angle-of-attack and the mean, deformed wing shape are not matched in common scaling and testing procedures), and the differing dynamic testing conditions between flight and wind tunnel. The wind-tunnel testing environment has much more moderate frequency 'turbulence' than atmospheric flight conditions, resulting in continuously disturbed model motions which mask the subtleties of LCO behavior. Several wind-tunnel tests have reported unintentional LCO behavior observed during aeroelastic/flutter testing: Gránásy et al.¹¹ found two branches of LCO behavior

extending well below the flutter boundary for a high aspect ratio, elastic, actively controlled wing model; NASA's ARW-2 (supercritical, high aspect ratio, Aeroelastic Research Wing)^{12,13} exhibited a region of 'high dynamic response' in its first wing bending mode; and NASA's High Speed Civil Transport (HSCT) Flexible Semispan Model¹⁴ exhibited two regions of 'LCO-like' response, one a broader region of 'high dynamic response' in the first bending mode and the other a narrow 'chimney' of 'high response.' At the highest tested pressure, flutter and model failure were encountered in this chimney region. The latter two cases, along with numerous other unsteady pressure experiments in the NASA Langley Transonic Dynamics Tunnel, are summarized in Ref. 15. One final recent wind-tunnel test is that of a two-dimensional pitching and plunging supercritical airfoil model.¹⁶ LCO behavior was measured that agreed with flutter motions calculated with a Navier-Stokes code and a frequency domain modal superposition flutter solution.

It is interesting to note a connection between the current focus on LCO phenomena and longstanding aeroelastic response behaviors such as buffeting and buffet onset, control surface buzz, and angle-of-attack effects. One of the first experimental studies of nonlinear transonic effects on flutter was Erickson's¹⁷ flutter and buffet tests of an early version of a space shuttle wing. Angle-of-attack and transition effects on damping were found over a very narrow transonic Mach range, and "limited amplitude flutter motions" and destructive wing flutter were encountered. Farmer, et al.¹⁸ studied the effect of supercritical and conventional wing profiles upon transonic flutter. Unpublished results of the effect of angle-of-attack upon flutter are similar in nature to those described above. Moss and Pierce¹⁹ document a case of torsional wing 'buzz' at buffet onset conditions on a solid steel model. For the 27-degree leading-edge wing sweep, the main wing shock and the separated flow behind it aligned with the torsion mode node line, providing the driving mechanism for the LCO.

Because of the difficulty of capturing LCO behavior in wind-tunnel tests, its occurrence in the tests of the typical business jet wing flutter model¹⁰ mentioned above led to its selection for further testing as the MAVRIC-I model. It is anticipated that this may be the first of a series of such research models. Due to its simple aluminum plate construction, the model has the strength to withstand large dynamic wing motions without failing, and making it ideal for the study of LCO behavior. This paper presents details of the model construction, refurbishment, and

instrumentation followed by a description of the data system utilized for measuring the wing response and unsteady wing pressures. Testing of the model with three different wingtip configurations, in both air and R134a heavy gas is discussed. Finally, test results are given in the form of calculated (linear aerodynamics) and experimental flutter boundaries, and maps of regions of LCO response behavior

MODEL CONSTRUCTION, REFURBISHMENT, AND INSTRUMENTATION

The MAVRIC flutter model has been tested previously in Langley's Transonic Dynamics Tunnel (TDT) in 1993 and 1994. It is a semispan model of a typical business jet design constructed of a stepped thickness aluminum plate planform and covered with end-grain balsa wood to provide the wing contour. The wing has no twist or dihedral, reflecting its original purpose of providing wind-tunnel flutter test data for calibration of analysis methods and it was tested on the tunnel sidewall, low-mounted on a fuselage body of revolution. The plate structural construction method results in flutter models with sufficient strength to withstand oscillation amplitudes much larger than more typical flutter model construction methods can withstand without sustaining damage. Inspection of the previous test results indicated that the model exhibited LCO behavior at the higher transonic Mach numbers tested. Thus the model was selected for retesting as the MAVRIC-I model.

Figure 1 shows the refurbished model mounted on the TDT sidewall. The refurbishments included: a new streamlined aft fuselage section, a new streamlined under-wing 'belly-pan' fairing, a new wingtip body of revolution for the 'clean wing' configuration, and instrumentation. The fuselage consists of bodies of revolution integrated with a 4-inch standoff section to account for the wall boundary layer. The original aft fuselage closure was a straight-sided conical section commencing at the wing trailing edge, which aggravated wing-fuselage juncture flow separation. The new aft fuselage was extended 6 inches and contained a 24-inch circular arc section closure with a sharp trailing edge. The new belly-pan closure was designed to minimize forward- and aft-facing curvatures and to meld smoothly with the wing lower surface.



Figure 1. MAVRIC-I model mounted on tunnel sidewall.

Figure 2a shows the wing planform and instrumentation layout (described below) while Figure 2b shows the stepped aluminum plate and end-grain balsa wood upper and lower surfaces. The plate thickness steps from 0.276 inches to 0.106 inches in four steps over the wingspan. The wing has a taper ratio of 0.29, a midchord sweep angle of 23 degrees, and a span, S , of 53.17 inches. The wing thickness varies from 13 percent (extrapolated to the symmetry plane) to 8.5 percent at the wingtip.




Figure 2. Layout of wing and instrumentation.

Figure 3 shows the three wingtip configurations tested: clean wingtip (body of revolution), pencil tipstore, and winglet. They are attached to the wingtip with three mounting screws. The winglet, also used in the 1994 test, is canted 75 degrees from the wing plane and has a 41 degree leading-edge sweep. The pencil tipstore was constructed to match the properties of the original winglet used in the 1993 test and thus has different mass properties than the present winglet.

The model is instrumented with 84 differential unsteady pressure sensors at three spanwise chords, 8 miniature piezoelectric accelerometers, and root bending and torsion strain gages. A servo-accelerometer measuring the model angle-of-attack was also mounted to the wing plate root. Bending and torsion strain gages were also bonded to the wing plate root inside of the fuselage housing, where the bolt restraints at the root caused the torsion strain gage to be ineffective.

Figure 4 shows the wing lower surface and fuselage. Also, routing troughs for the instrumentation are visible on the lower wing surface. The upper surface (not shown) has similar instrumentation routings. The 4-inch standoff of the fuselage from the wind-tunnel wall is clearly visible. Spanwise measurements are referenced to Buttock Line 0.00 inches, which is located at the centerline of the fuselage body of revolution, abutting the standoff.



Figure 3. Wingtip configurations tested: winglet, pencil tipstore, and clean wingtip.




Figure 4. View of lower wing and fuselage mounted on tunnel sidewall.

Eight accelerometers were mounted to the bottom of the wing plate at locations as near as allowed by the wing contour thickness to the leading and trailing edges at span stations $y = 14, 24, 36$ and 48 inches ($y/S = 0.26, 0.45, 0.68, 0.90$). The wing contour at these locations was restored by filling the cavities with a silicone sealant. This filling resulted in detrimental straining of the accelerometer casings under strained conditions and in situ calibrations of the accelerometers were required. Also, optical targets were installed on the wing lower surface for use by the Videogrammatic Model Deformation System.²⁰ This system was capable of recording dynamic model deformations at a rate of 60 frames per second. Late in the test the wing upper surface was tufted in order to visually observe the extent of flow separation and make correlations with regions of LCO activity.

An attractive detail of the MAVRIC-I model construction and instrumentation procedures is their low cost relative to standard procedures. While the structural metal plate and end-grain balsa wood fabrication method is not favored for models requiring similitude with full-scale aircraft, it is quite adequate in producing models devoted to computational method validation and is much less expensive. A similar economy was followed in selecting the method for instrumenting the model. With the end-grain balsa wood in place and no desire to modify the wing profile (the LCO behavior of the model was to be preserved), the decision was made to

install instrumentation using minimally invasive surface routing of the balsa wood. Figure 5 shows the routing troughs for the mid and outboard upper surface chords of pressure sensors during fabrication.




Figure 5. Upper surface pressure sensor installation showing routing channels during refurbishment of model.

Figure 6 indicates the method for assembling the pressure sensor mounting blocks, which included the 0.020-inch surface orifices. Shown from the bottom to the top are a pressure sensor, a protective metal sleeve, a mounting block with orifice hole, and the assembled mounting. The 0.5 inch long 2.0 psi. differential sensors were sealed inside the protective sleeves, which were then sealed into the mounting




Figure 6. Unsteady pressure sensor installation components: bottom to top – pressure sensor, protective metal sleeve, rectangular mounting block with orifice hole, and assembled fixture.

blocks already installed in the wing and covered with a filler material. The routed troughs containing reference pressure tubing and electrical wiring were covered with balsa strips and smoothed to the wing contour. The sensor reference tubes were connected to pressure manifolds located in the routed troughs. The manifolds were connected to the wind-tunnel plenum chamber by tubing. The three chords of pressure sensors were located at span stations $y = 11.5, 33.5, \text{ and } 46.5$ inches ($y/S = 0.22, 0.63, \text{ and } 0.87$). At each station, 18 upper surface and 10 lower surface pressure orifices were located as indicated in Table 1. In the following sections, upper (U) and lower (L) surface pressures and pressure coefficients are labeled for the Inboard (I), Middle (M), and Outboard (O) (e. g., PMU_{44} and $CPMU_{44}$ for the upper, middle sensor measurement at $x/C = 0.44$).

Following completion of the installation of the instrumentation, the wing surface was smoothed where required with filler material to restore the model to its original contours. With end-grain balsa wood construction, it is not possible to achieve the high quality surface finish typically required for performance wind-tunnel testing. However, a good quality surface finish was achieved, and the final wing surface was surveyed to provide coordinates for computational code validations. The model was not painted for this test due to concern over protection of the pressure sensor orifices and the surface finish near the orifices. Finally, upper and lower surface transition grit strips were applied. The #80 grit strips were located at five percent chord and were approximately 0.25 inches wide.

STRUCTURAL MODELING AND VIBRATION TESTING

The MSC NASTRAN Finite Element Model (FEM) of the clean wing (wing with no tip) configuration from the earlier tests was modified for the current test. In the FEMs, the aluminum plate is represented by plate elements with plate thickness based on measured values. Plate elements representing the end-grain balsa wood, with thickness based on the airfoil shape, are superimposed on the aluminum plate elements. The same balsa properties derived for use in the earlier FEM were used and rendered good quality results in terms of mass and stiffness. New FEMs were constructed for all three of the current tip configurations. Plate and concentrated mass elements were used for the clean wingtip and winglet, and beam elements with concentrated masses were used for the tipstore. The final measured and NASTRAN model weights were 24.25, 24.46, and 24.53 lb for the

Table 1. Unsteady pressure orifice locations for Inboard, Middle, and Outboard pressure chords.

Upper x/C	Lower x/C
0.03	
0.07	0.07
0.11	0.11
0.16	
0.22	0.22
0.30	0.30
0.38	0.38
0.44	
0.50	0.50
0.55	
0.60	0.60
0.65	
0.70	0.70
0.76	
0.82	0.82
0.88	
0.94	0.94
1.0	

clean wingtip, tipstore, and winglet configuration, respectively.

Vibration tests were conducted before the wind-tunnel test and periodically (wind-off) during the test. Table 2 gives the pre-test analytical and experimental bending and torsion mode frequencies and experimental measured damping values for the three wingtip configurations tested. The clean wingtip modal displacements and node lines for the first two bending and torsion modes are shown in Figure 7. Due to the large wing displacements anticipated for the test, attention was given to ensure that clearances at the wing root were adequate to prevent any rubbing or binding. Large amplitude free decay records indicated smooth damping in the first bending mode, decreasing from 1.5 percent for ± 2.5 -inch deflections to 1 percent at the lowest amplitudes.

The aggressive LCO testing led to some cracks developing in the balsa wood, predominantly in the inboard region of the wing. This was reflected in small changes noted in modal frequencies from the wind-off vibration tests made during the test. For the clean wingtip configuration, the three lowest frequency modes varied from 4.07 to 3.91, from 14.04 to 12.75, and from 31.76 to 30.32 respectively, over the duration of the test.

TRANSONIC DYNAMICS TUNNEL

The TDT is a closed circuit, continuous-flow wind tunnel capable of testing at stagnation pressures from near zero to atmospheric conditions and over a Mach number range from zero to 1.2. The test section of the TDT is 16 feet square with cropped corners. Controlled variation of pressure in the tunnel simulates variations in flight altitude. Tests can be performed in the TDT using air as the test medium; however, the most distinguishing feature of the tunnel is the use of a heavy gas, presently R-134a refrigerant. R-134a is about four times as dense as air, yet has a speed of sound of about half that of air. These properties of higher density and lower sonic speed have beneficial effects on the design, fabrication, and testing of aeroelastically scaled wind-tunnel models. Other advantages resulting from the use of a heavy gas are a nearly three-fold increase in Reynolds number and lower tunnel drive horsepower requirements.

DATA ACQUISITION SYSTEM

Two digital Data Acquisition Systems (DAS) were utilized during the test. The primary system, DAS E, sampled 107 signals, all those discussed above plus several tunnel parameters and reference sine waves, at 1000 samples per second (sps). Analog antialiasing prefilters set at 200 Hz. were used on all channels. The second system, DAS D, sampled a subset of 30 instrumentation signals at 5000 sps using 1000 Hz. prefilters. The DAS D system was intended as a backup for DAS E and to provide information on any high frequency behavior above the 200 Hz. cutoff of the DAS E data. Approximately 1100 tunnel test points were acquired during the test, consisting of test

Table 2. Analytical and experimental structural normal mode frequencies for the three configurations tested.

(a) Clean Wingtip			
Mode	Analysis	Experiment	
	F, Hz.	F, Hz.	Damping, percent
1B	4.08	4.072	1.131
2B	13.97	14.043	1.154
1T	31.54	31.757	0.835
3B	31.99	32.591	1.154
2T	58.11	57.791	0.863
4B	58.79	61.887	1.032
3T	88.23	90.871	0.864
5B	92.21	97.57	1.51

(b) Pencil Tipstore			
Mode	Analysis	Experiment	
	F, Hz.	F, Hz.	Damping, percent
1B	3.68	3.942	1.533
2B	12.89	13.336	1.08
3B	28.91	30.407	1.118
1T	30.53	31.29	0.764
2T	48.73	53.02	1.009
4B	53.97	58.55	1.1224
	71.06	77.61	1.7

(c) Winglet			
Mode	Analysis	Experiment	
	F, Hz.	F, Hz.	Damping, percent
1B	3.78	3.815	1.32
2B	11.99	12.294	1.21
3B	25.14	26.279	1.128
1T	30.27	31.027	1.114
Winglet	43.33	45.99	1.039
2T	48.19	50.29	0.948
	62.82	69.66	0.771
	73.14	74.71	0.816




Figure 7. Mode shapes and node lines for the first two bending and torsion modes of the clean wingtip configuration.

Tab Points (TP) and flutter Bypass Points (BP). At Tab Points, 10 seconds of data were acquired on both of the DAS systems. Since the TDT is devoted to flutter model testing, it is provided with a 'Bypass Valve' system that can rapidly decrease the test section dynamic pressure by venting the back-leg of the tunnel circuit to the plenum chamber. The system is activated via a trigger by test personnel in the control room who are monitoring model activity. The data system contains a 'circular file' that continuously maintains data for the preceding minute of the test. Activation of the Bypass Valves initiates acquisition of a BP data point by the DAS. This point consists of


the one minute of data recorded prior to and one minute of data acquired following the BP event.

RESULTS


In the present paper, only an overview of the test results will be given. The calculated and experimental flutter boundaries are given for the model in air and heavy gas, followed by a discussion of the flutter and LCO behaviors observed. Finally, maps of the LCO behavior of the model at dynamic pressures of 50-100 pounds per square foot (psf) are given, along with samples of time histories and wing pressure coefficients.

During testing, typical TDT flutter testing procedures were followed. The wing root bending strain gage was monitored to ensure that limiting bending moments of 2600 in.-lb. were not exceeded. Early testing established the root angle of attack for near-zero wing loading as $\alpha = 0.6$ deg. Subsequent testing was performed for the three wingtip configurations at this angle and at increments of +1.0 and +1.5 deg, that is, for $\alpha = +0.6, +1.6,$ and $+2.1$ deg. Testing was performed at constant tunnel total pressures, typically beginning at the lowest pressure to be tested for a given run and proceeding to higher pressures by 'bleeding' in air or heavy gas. At each pressure, tunnel test conditions were established by varying fan speed (RPM) which simultaneously varied tunnel Mach number and test section dynamic pressure.


Initial testing at lower dynamic pressures was conducted up to $M = 1.2$. Generally, model response was benign above $M \sim 0.96$ and subsequent testing focused on Mach numbers up to 1.0. Figures 8a and 8b give the flutter boundaries in air and heavy gas for the three wingtip configurations calculated using the FEMs and linear doublet lattice aerodynamics. Figure 8a also includes the limited number of experimental flutter points that were obtained in air. Figure 8c presents the corresponding experimental boundaries for heavy gas. The calculated results show similar trends with Mach number for the model in air and heavy gas, with the flutter boundary in air being about 20 psf lower than in heavy gas. The calculated flutter frequencies are similar for air and heavy gas, dropping from 12-14 Hz. at $M = 0.6$ to about 10 Hz at $M = 0.95$. The experimental results in heavy gas (Figure 8c) show similar trends with each wingtip configuration but deviate from the linear calculations for the higher Mach numbers where the slopes of the experimental results are steeper. At $M = 0.6$ there is good agreement with the linear analysis.



a. Analysis and experiment ($\alpha = 0.6$ deg.), air.



b. Analysis, R-134a heavy gas.



c. Experiment, R-134a heavy gas, $\alpha = 0.6$ deg.

Figure 8. Flutter boundaries and frequencies in air and heavy gas.

for the flutter dynamic pressure, Q_f , and frequency, f_f . However, at $M \sim 0.90$ the experimental values of Q_f and f_f have dropped to about 85 psf and below 8 Hz, respectively, well below the corresponding values from the analysis. Figure 9 shows the aft wingtip accelerometer time history recorded during a typical BP flutter point at $M_f = 0.856$, $Q_f = 92$ psf, and $\alpha = 0.6$ deg. for the tipstore configuration. The peak amplitude of ± 20 g's, when the Bypass Valves were fired, corresponds to wingtip displacements of ± 2.9 inches for this $f_f = 8.2$ Hz flutter motion. The flutter analysis indicates that the flutter mode results predominantly from the coalescence of the wind-off first bending and torsion modes at $f = 3.68$ and 29.91 Hz, respectively for this configuration. The highest f_f measured during the test was at the highest dynamic pressure flutter point in heavy gas ($M_f = 0.595$ and $Q_f = 165$ psf) where $f_f = 12.5$ Hz.




Figure 9. Sample of an aft wingtip accelerometer response at a flutter condition, pencil tipstore in heavy gas: $M_f = 0.856$, $Q_f = 92$ psf., $\alpha = 0.60$ deg.

The behavior of the model when approaching 'flutter' and 'LCO' points throughout the Mach range 0.60-0.95 was of interest since it involved elements familiar to flutter test engineers and central to this test: pseudo-random wing response to tunnel turbulence, 'bursting' and beating wing motions, rapid onset of 'diverging' wing oscillations, and the monotonic growth of wing oscillations to constant amplitude which is the signature of Limit Cycle Oscillations. Response to tunnel turbulence is termed pseudo-random here since there is correlation with tunnel disturbances, particularly at frequencies below 100 Hz. Bursting wing motions are commonly observed during approaches to flutter conditions and are typified by sudden growth of wing oscillations, typically of the subcritical flutter mode, whose

amplitudes crest and then subside. The duration of these bursts, which occur with irregular intervals, is viewed as an indicator of approaching flutter onset. Beating wing motions are mentioned since they were observed during this test. This behavior is more regular than in bursting, and is usually associated with closely spaced frequency components. The distinction between these latter two behaviors in practice can be difficult. In general, for Mach numbers between 0.60-0.85 the Mach number interval between the start of bursting behavior and flutter onset or LCO behavior grows with increasing Mach number. For lower speeds in this range, this difference is small and what is generally termed 'classical flutter onset' is observed. That is, over a short interval of increasing Mach number or dynamic pressure, exponentially diverging wing motions are encountered that usually lead to wing failure unless corrective action is taken. At the higher speeds in this range this difference in Mach number becomes larger and the situation becomes increasingly fuzzy. It is in this region of $M \sim 0.85$ -0.95 where LCO behavior, which does not fit the classical flutter onset model, is encountered for the MAVRIC-I model.

Figures 10 and 11 present experimental data from a series of test points for conditions near the bottom of the transonic 'flutter dip'. The data is for the clean wingtip configuration at $\alpha = 0.6$ deg in heavy gas. Figure 10 presents aft wingtip accelerometer time histories illustrating the model behavior elements discussed above while Figure 11 presents pressure coefficient, C_p , distributions for the outboard row of sensors at the corresponding conditions. The ranges covered are $M = 0.881$ -0.95 and $Q = 80.7$ -89.8 psf. The $M = 0.881$ condition (Figs. 10a and 11a) is just below the onset of bursting activity and is characterized by low level 'pseudo-random' activity in all structural modes up to 200 Hz with the preponderance of activity in the 1st and 2nd bending modes (1st bending wind-on frequency, f_{1B} , is 7.8 Hz). Flow at the outboard chord of pressures is intermittently separated at all but the highest Mach number. This is shown in Figure 11e by the trailing edge $-C_p$ minimum level rising above 0.0 psi while the maximum level remains below 0.0 psi. At $M = 0.89$ bursting activity in the 1st bending mode is seen (Figure 10b) with durations reaching 1-3 seconds and $f_{1B} = 7.5$ Hz. At this condition, the pressure level minima at the midchord trailing edge, CPU_{100} (not shown), has decreased to 0.0, indicating that the region of separated flow has spread towards midchord. Fully developed LCO occurs at $M = 0.895$ with an average LCO amplitude of about 12 g's and

with $f_{IB} = 7.3$ Hz. A decreasing frequency of f_{IB} with increasing Mach number has been noted in previous studies documenting high wing response transonic behaviors^{12,13} and it is demonstrated here as well. As the separated flow region continues to grow with Mach number increasing from 0.913 to 0.95, f_{IB} drops from 7.1 Hz to 6.6 Hz. Beating behavior is seen at $M = 0.913$ while the response at $M = 0.95$ is much calmer, very similar to that at $M = 0.881$. Note that at the LCO condition, $M = 0.895$, the trailing-




Figure 10. Sequence of aft wingtip accelerometer responses exhibiting pseudo-random, bursting, Limit Cycle Oscillation, and beating responses: Clean wingtip, heavy gas, $\alpha = 0.6$ deg.




Figure 11. Sequence of pressure coefficient distributions from outboard pressure chord at Tab Points shown in Figure 10: mean, minimum, and maximum coefficient values.

edge wingtip flow on both the upper and lower surfaces is intermittently separating and reattaching, whereas at $M = 0.95$ with the upper and the lower aft surfaces fully separated at the wingtip (Figure 11e) the response is benign. Three features which distinguish LCO wind-tunnel testing from flight testing are the test environment, the sensitivity of the LCO behavior, and the wing loading condition. A good portion of the nonstationary nature of the response shown in Figure 10 is related to the wind-tunnel test environment. Transonic wind tunnels (even those with documented good flow control and quality) are inherently ‘noisy’ in the frequency range 0-100 Hz where all aeroelastic testing is focused. This is in contrast to the flight test environment where disturbance levels in the 0-100 Hz. range are well below those of wind-tunnels. Secondly, a feature seen repeatedly in this test was the sensitivity of the bursting, beating, and LCO behaviors to changing tunnel conditions. A consistent observation was that when transitioning from one stabilized tunnel condition to another, these dynamic behaviors were invariably accentuated, usually subsiding to lower levels once conditions were stabilized. This was true even for quite slow adjustments to tunnel condition (accomplished with a low rate of fan RPM changes). Thus this LCO behavior appears to be due to a very fine balance of forces on the wing, occurring at conditions of intermittent flow separations over wing regions of dominant modal motions (e.g., the wingtip region here for the 1st bending and torsion modes).

Finally, the wing loading condition in flight is an important parameter that is very rarely matched in aeroelastic wind tunnel testing due to the varying similitude requirements for matching model strength versus stiffness. Thus flutter models are usually tested near unloaded wing conditions ($\alpha \sim 0$) and not near a 1-g statically deformed wing shape which similitude with the 1-g flight test would require. In the LCO maps discussed next, the effect of angle-of-attack on LCO behaviors is seen to be considerable.

Visual inspection of strip chart time histories for the two wingtip accelerometers was used to identify regions of bursting, beating, and LCO behavior. Maps of these behaviors are presented in Figures 12 and 13 for the three wingtip configurations tested in heavy gas and air, respectively. The maps cover the three angles tested and the dynamic pressure range from 50-100 psf. The Mach number range shown is 0.82 to 0.96. Although the model was tested, at the lower pressure levels, to $M = 1.2$, no LCO behavior was observed above $M = 1.0$. Severe Reynolds

number and/or transition effects, evident in comparing mean wing pressures for air and heavy gas (not shown), were seen at $Q = 50$ psf. This effect was also noticeable at 75 psf but was not seen at 100 psf. Thus, the LCO map for air, Figure 13, should be used with caution, while that for heavy gas, Figure 12, is believed to be reliable for transonic flow with turbulent boundary layer flow. On the other hand, comparison of the two figures provides insight into the effect of the test gas on LCO behavior, with particular focus upon the effect of the speed of sound, and thus the reduced frequency, on LCO for a given model.

Numbers attached to boundaries in the Figures 12 and 13 give the half-amplitude LCO g-levels for the region denoted by the boundary. Regions of bursting and beating activity are denoted with ‘B’. The dominant LCO behavior of the model was in the 1st bending mode, while LCO involving the 1st torsion mode was found for a narrow Mach number range during testing in air. Some regions of small amplitude LCO response of the 2nd bending mode were also observed. Boundaries at the 100 psf level in these figures obviously merge with the flutter boundaries presented in Figure 8 and define what has traditionally been referred to as the bottom of the ‘transonic dip’. This emphasizes the difficulty in distinguishing between flutter and large amplitude LCO behavior in such regions. Many of these ‘flutter points’ in Figure 8 actually were LCO points, even though the amplitude of the wing response led to Bypass Valve action. Likewise, there were a number of test conditions in the LCO map regions of Figures 12 and 13 where the Bypass Valve was used. Absence of boundaries in certain map regions should not be taken as implying benign response. Due to the complexity of the LCO behaviors, limitations in number of test points achievable, and concern for model integrity, the coverage of conditions in the maps is neither complete nor continuous.

A consistent feature of the maps, which has been observed elsewhere^{2,12-14}, is LCO behavior occurring at constant Mach number over a range of dynamic pressure. Narrowness of these regions leads to use of the term ‘chimneys’ in describing them. A feature notable in the maps is the trend of the dominant 1st wing bending LCO ‘chimney’ with angle-of-attack. In heavy gas, Figures 12a and 12b show the Mach number associated with this chimney increasing from $M_{LCO} \sim 0.90$ at $\alpha = 0.6$ deg. to $M_{LCO} \sim 0.92$ at $\alpha = 2.1$ deg. In contrast to this trend, in air (Figure 13a and




Figure 12. Maps of Limit Cycle Oscillation regions for model in heavy gas. Indices give half-amplitude levels of aft wingtip accelerometer response in g's; 'B' indicates bursting/beating response.




Figure 13. Maps of Limit Cycle Oscillation regions for model in air. Indices give half-amplitude levels of aft wingtip accelerometer response in g's; 'B' indicates bursting/beating response.

13b) this LCO chimney decreases in Mach number from $M_{LCO} \sim 0.89$ at $\alpha = 0.6$ deg. to $M_{LCO} \sim 0.87$ at $\alpha = 2.1$ deg. A striking difference in the LCO behaviors of the model in air versus heavy gas is the occurrence of 1st torsion mode LCO response in air but not in heavy gas. This occurs consistently in air at $M \sim 0.91$ for all three configurations and all angles-of-attack. It is possible that this is due to the differing reduced frequencies caused by speed of sound differences in the two gases. The speed of sound in R134a heavy gas is about one-half that in air. Frequency spectra (not shown) of pressures in the vicinity of the shock on the upper surface show energy concentrations at 15-30 Hz in air and 5-15 Hz in heavy gas for data points near $M = 0.91$. These features vary strongly with Mach number. For data points near $M = 0.88$, they are seen at 20-40 Hz in air and 15-25 Hz in heavy gas. For $M = 0.91$, these frequencies result in reduced frequency values of about $k = \omega b/U \sim 0.07$ with b chosen as the semichord at the midchord row of pressure sensors. This value is at the low end of the range of reduced frequencies of self-excited shock oscillations that have been measured on airfoils¹⁰. Thus a possible coupling mechanism for the 1st torsion LCO seen here in air is interaction between shock oscillations and the torsion mode near 30 Hz, whereas for the same Mach number in heavy gas, the shock oscillation feature is closer to the 1st bending mode wind-on frequency near 10 Hz.

DISCUSSION OF COMPUTATIONAL CODE VALIDATIONS

Computational Fluid Dynamics (CFD) codes have held promise of computing transonic aeroelastic features for many years. Reference 21 documents the status of applications in this area. At issue has been achieving the proper level of flow modeling with an economical code capable of performing the numerous computer runs necessary to demonstrate method maturity. The highest code levels encompassing the various implementations of the Navier-Stokes equations have been too expensive in terms of computer cost and runtimes, up to the present, allowing only a small number of sample applications even for attached flow transonic cases. These issues are intensified when considering requirements for resolving the shock-boundary layer interactions necessary to compute large amplitude LCO cases like those presented herein. Capability to treat unsteady shock-boundary layer interactions for separating and reattaching flows would appear to be a necessity. Inviscid methods are not reliable for such LCO

applications.¹⁰ Perturbation methods based on steady viscous flows may be useful in predicting onset boundaries, but are unlikely to be useful in determining LCO amplitudes.

Reference 10 reports LCO calculations for the 1993 test of the MAVRIC-I model using an interactive quasi-steady boundary layer method coupled with a Transonic Small Disturbance code. Large amplitude LCO simulations are shown for $M = 0.888$, $Q = 79$ psf and $\alpha = 0.2$ deg. The calculations agreed well with the observed model frequency and amplitudes (about 3 inches half-amplitude wingtip motion) for this test condition in air. The calculation also agrees well with the LCO map from the current test: this condition is contained within the 1st wing bending LCO region of Figure 13a ($\alpha = 0.6$ deg.). Thus, this data set provides excellent code validation test cases for the important class of flow conditions involving shock-induced transonic flow separation onset at low wing angles, including Limit Cycle Oscillation behavior.

CONCLUDING REMARKS

The Models for Aeroelastic Validation Research Involving Computation model (MAVRIC-I), a business jet wing-fuselage semi-span flutter model, was tested in NASA Langley's Transonic Dynamics Tunnel with the goal of obtaining experimental data suitable for Computational Aeroelasticity code validation at transonic separation onset conditions. The inexpensive aluminum plate/balsa wood construction and instrumentation procedures are notable in this research model, and similar procedures are being considered for future research model projects. Unsteady pressures and wing responses were obtained for three wingtip configurations: clean, tipstore, and winglet. Traditional flutter boundaries were measured over the range of $M = 0.6$ to 0.9 and maps of Limit Cycle Oscillation behavior were made in the range of $M \sim 0.85$ to 0.95 . Effects of dynamic pressure and angle-of-attack were measured. Testing in both R134a heavy gas and air provided unique data on Reynolds number, transition effects, and the effect of the speed of sound on LCO behavior. The data set provides excellent code validation test cases for the important class of flow conditions involving shock-induced transonic flow separation onset at low wing angles, including Limit Cycle Oscillation behavior.

ACKNOWLEDGEMENTS

This work was supported by the NASA Aerospace Systems Concepts to Test (ASCoT) program. The authors wish to acknowledge Gulfstream Aerospace

of Savannah, Georgia for providing the semispan business jet wing flutter model and the SEEK EAGLE Office, Eglin Air Force Base, Florida for support of the structural dynamic modeling and testing, and the wind tunnel testing.

REFERENCES

1. Bunton, R. W. and Denegri, C. M. Jr.: Limit Cycle Oscillation Characteristics of Fighter Aircraft. *Journal of Aircraft*, Vol. 37, No. 5, September-October 2000, pp. 916-918.
2. Denegri, C. M. Jr.: Limit Cycle Oscillation Flight Test Results of a Fighter with External Stores. *Journal of Aircraft*, Vol. 37, No. 5, September-October 2000, pp. 761-769.
3. Cunningham, A. M. Jr.: The Role of Non-Linear Aerodynamics in Fluid-Structure Interaction. AIAA Paper No. 98-2423, June 1998.
4. Cunningham, A. M. Jr.: A Generic Nonlinear Aeroelastic Method With Semi-Empirical Nonlinear Unsteady Aerodynamics, Volume I. Technical Discussion. AFRL-VA-WP-TR-1999-3014, February 1999.
5. Meijer, J. J. and Cunningham, A. M. Jr.: Outline and Applications of a Semi-Empirical Method for Predicting Transonic Limit Cycle Oscillation Characteristics of Fighter Aircraft. *Proceedings of International Forum on Aeroelasticity and Structural Dynamics*, Manchester, U. K., Royal Aeronautical Society, 1995, vol. 2, pp. 75.1-75.19.
6. Meijer, J. J.: Determination of Transonic Unsteady Aerodynamic Loads to Predict the Aeroelastic Stability of Fighter Aircraft. *Proceedings of CEAS International Forum on Aeroelasticity and Structural Dynamics*, Rome, Italy, Associazione Italiana di Aeronautica ed Astronautica, 1997, vol. 2, pp. 373-383.
7. Norton, W. J.: Limit Cycle Oscillation and Flight Flutter Testing, *Proceedings of the 21st Annual Symposium*, Society of Flight Test Engineers, Lancaster, CA. 1990, pp. 3.4.4-3.4-12.
8. Jacobson, S. B., Britt, R. T., Dreim, D. R., and Kelly, P. D.: Residual Pitch Oscillation (RPO) Flight Test And Analysis on the B-2 Bomber. AIAA Paper No. 98-1805, April 1998.
9. Dreim, D. R., Jacobson, S. B., and Britt, R. T.: Simulation of Non-Linear Transonic Aeroelastic Behavior on the B-2. NASA CP-1999-209136 Part 2, CEAS/AIAA/ICASE/NASA Langley International Forum on Aeroelasticity and Structural Dynamics, Williamsburg, USA, 1999, pp. 511-521.
10. Edwards, J. W.: Calculated Viscous and Scale Effects on Transonic Aeroelasticity. Paper No. 1 in AGARD R-822, March 1998.
11. Gránásy, P., Matsushita, H. and Saitoh, K.: Nonlinear Aeroelastic Phenomena at Transonic Region. CEAS Rome June 1997. *Proceedings of CEAS International Forum on Aeroelasticity and Structural Dynamics*, Rome, Italy, Associazione Italiana di Aeronautica ed Astronautica, 1997, vol. 3, pp. 379-385.
12. Eckstrom, C. V., Seidel, D. A., and Sandford, M. C.: Unsteady Pressure and Structural Response Measurements on an Elastic Supercritical Wing. *J. of Aircraft*, Vol. 27, No. 1, January 1990, pp. 75-80.
13. Eckstrom, C. V., Seidel, D. A., and Sandford, M. C.: Measurements on Unsteady Pressure and Structural Response for an Elastic Supercritical Wing. NASA TP 3443, November 1994.
14. Silva, W. A., Keller, D. F., Florance, J. R., Cole, S. R., and Scott, R. C.: Experimental Steady and Unsteady Aerodynamic and Flutter Results for HSCT Semispan Models. AIAA Paper No. 2000-1697, April, 2000.
15. Schuster, D. M., Scott, R. C., Bartels, R. E., Edwards, J. W., and Bennett, R. M.: A Sample of NASA Langley Unsteady Pressure Experiments for Computational Aerodynamics Code Evaluation. AIAA Paper No. 2000-2602, June 2000.
16. Knipfer, A and Schewe, G.: Investigations of an Oscillating supercritical 2D Wing Section in a Transonic Flow. AIAA Paper No. 99-0653, January 1999.
17. Erickson, L. L.: Transonic Single-Mode Flutter and Buffet of a Low Aspect Ratio Wing Having a Subsonic Airfoil Shape. NASA TN D-7346, January 1974.
18. Farmer, M. G., Hanson, P. W., and Wynne, E. C.: Comparison of Supercritical and Conventional Wing Flutter Characteristics. *Proceedings of the 17th AIAA Structures, Structural Dynamics, and Materials Conference*, King of Prussia, PA., May 1976, pp. 608-614.
19. Moss, G. F. and Pierce, D.: The Dynamic Response of Wings in Torsion at High Subsonic Speeds, AGARD CP-226, 1977.
20. Burner, A. W.: Model Deformation Measurements at NASA Langley Research Center. Paper number 34 in AGARD CP 601, May 1998.
21. Numerical Unsteady Aerodynamic and Aeroelastic Simulation. AGARD R-822, March 1998.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE May 2001	3. REPORT TYPE AND DATES COVERED Technical Memorandum	
4. TITLE AND SUBTITLE MAVRIC Flutter Model Transonic Limit Cycle Oscillation Test		5. FUNDING NUMBERS WU 706-31-41-02	
6. AUTHOR(S) John W. Edwards, David M. Schuster, Charles V. Spain, Donald F. Keller, and Robert W. Moses			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NASA Langley Research Center Hampton, VA 23681-2199		8. PERFORMING ORGANIZATION REPORT NUMBER L-18082	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001		10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA/TM-2001-210877	
11. SUPPLEMENTARY NOTES This paper was presented at the 42 nd AIAA/ASME/ASCE/AHS Structures, Structural Dynamics, and Materials Conference, April 16-19, 2001, Seattle, Washington, AIAA Paper No. 2001-1291.			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 05 Distribution: Nonstandard Availability: NASA CASI (301) 621-0390		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The Models for Aeroelastic Validation Research Involving Computation semi-span wind-tunnel model (MAVRIC-I), a business jet wing-fuselage flutter model, was tested in NASA Langley's Transonic Dynamics Tunnel with the goal of obtaining experimental data suitable for Computational Aeroelasticity code validation at transonic separation onset conditions. This research model is notable for its inexpensive construction and instrumentation installation procedures. Unsteady pressures and wing responses were obtained for three wingtip configurations: clean, tipstore, and winglet. Traditional flutter boundaries were measured over the range of $M = 0.6$ to 0.9 and maps of Limit Cycle Oscillation (LCO) behavior were made in the range of $M = 0.85$ to 0.95 . Effects of dynamic pressure and angle-of-attack were measured. Testing in both R134a heavy gas and air provided unique data on Reynolds number, transition effects, and the effect of speed of sound on LCO behavior. The data set provides excellent code validation test cases for the important class of flow conditions involving shock-induced transonic flow separation onset at low wing angles, including Limit Cycle Oscillation behavior.			
14. SUBJECT TERMS MAVRIC; Transonic; Limit cycle oscillation; Transonic Dynamics Tunnel		15. NUMBER OF PAGES 20	
		16. PRICE CODE A03	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL